

## C6 micro-BF/W (vs)



Technical Characteristics	Value		Units
	C6	C6 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	8.5	8.7	A
AC Line power	5.9	6.6	kVA
Pump water flow (cooling)		100	l/m
Pump water flow (transfer)		67	l/m
Differential pressure available (cooling) (to be added to the network pressure)		4.4 <small>(if pressure at 2.0 – Total 6.4)</small>	bar
Pump Pressure (transfer)		4.8	bar
Water tank capacity		30	l
Water output temp.		Network temp.	-
Hydraulic connections		1" F	-
Compressed air connection		1" F	-
Compressed air max pressure		7	bar
<b>Enclosure</b>			
Length, Width, Height		897 x 442 x 752	mm
Weight empty		115	kg
Color		RAL 7035 & black	
<b>Option</b>			
	<b>Bolting to floor</b>	<b>Wheels</b>	
C6-BF	YES	NO	
C6-W	NO	YES	

An ultra-compact mold cooling unit designed for heat and cool processes.

- Efficient** Customized for heat and cool processes through mold cooling and purging solution.
- Easy to use** Entirely remote controlled and powered by Roctool RT series.
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

*Roctool S.A. reserves the right to change technical specifications without notice.*

**Roctool SA**  
Savoie Technolac – Modul R  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
France  
**+33 479 26 27 07**