

R30 micro-BF/W (vs)



Technical Characteristics	Value		Units
	R30	R30 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	4.5	4.5	A
AC Line power	3.1	3.5	kVA
Cooling capacity of exchanger	30		kW
Inlet temperature (from factory)	20-25		°C
Outlet temperature (to process)	28-33		°C
Primary Hydraulic connections	1" F BSP		-
Secondary Hydraulic connections	3/4" F		-
Water tank capacity	30		l
Secondary water flow	58		l/min
Primary fluid flow (pump excluded)	58		l/min
Pressure available	4.9		bar
Enclosure			
Length, Width, Height	900 x 300 x 760		mm
Weight empty	70		kg
Color	RAL 7035 & black		
Option			
	Bolting to floor	Wheels	
R30-BF	YES	NO	
R30-W	NO	YES	

An ultra-compact cooling unit designed for Roctool induction generators.

- Efficient** Ultra Compact hydraulic module adapted for cooling ROC series through two closed water loop.
- Easy to use** Entirely remote controlled by Roctool RT series (HMI).
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

R
Roctool SA
Savoie Technolac – Modul R
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
France
+33 479 26 27 07