

# ROC-E 100



Technical Characteristics	Value	Units
Power	100	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	134	KVA max
Frequency Range	20-60	KHZ
Water Flow	24	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	¾" M	Inch
Color	RAL 7035 Grey	
<b>Generator enclosure</b>		
Length, Width, Height	600 x 500 x 1600	mm
Weight	250	kg
<b>Connection Box enclosure</b>		
Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An induction generator dedicated for Roctool processing.

- \ **Compact** ROC-E's design saves valuable floor space and simplifies in-line integration.
- \ **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- \ **Secured** ROC-E 100 steel cabinet and shielded electrical cables prevent from electromagnetic disturbance for nearest equipment.

*Roctool S.A. reserves the right to change technical specifications without notice.*

\  
 Roctool SA  
 Savoie Technolac – Modul R  
 34 Allée du lac d'Aiguebelette  
 73370 Le Bourget du Lac  
 France  
 +33 479 26 27 07