

ROC-E 150 DZ



Technical Characteristics	Value	Units
Power	2 x 150	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	389	KVA max
Frequency Range	20-60	KHZ
Water Flow	36	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	3/4" M	Inch
Color	RAL 7035 Grey	
Generator enclosure		
Length, Width, Height	600 x 500 x 1600	mm
Weight	250	kg
Connection Box enclosure		
Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An induction generator dedicated for Roctool processing.

- \ **Double Zone** The double zone version features two independent power outputs that can operate simultaneously under identical or different parameters.
- \ **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- \ **Secured** ROC-E 150DZ steel cabinet and shielded electrical cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

\
 Roctool SA
 Savoie Technolac – Modul R
 34 Allée du lac d'Aiguebelette
 73370 Le Bourget du Lac
 France
 +33 479 26 27 07